

# PLUS 3P

Single, Duplex and Triplex housings for cartridges with standard SX flat seals (DOE) and for specialty cartridges with BX and CX quick-fit double o-ring.



SENIOR TRIPLEX TS

IN/OUT connections 1/2", 3/4", 1", 1 1/4", 1 1/2", with brass or plastic BSP threads; models with NPT plastic threads 3/4", 1".

**Range of models:** Medium, Junior, Senior, Master for cartridge heights 5", 7", 10", 20".

Models with transparent (TS) or opaque (AB) bowls.

**M** models with 2 manometers.

**S** models Senior (10") and Master (20") with discharge valve for self-cleaning performance, provided with a drain funnel to protect potable water from back-flow pollution, in compliance with UNI EN 1717 - 11/2002.

**MP** models with plastic male IN/OUT connections BSP threads.

For cartridges with BX and CX quick-fit double o-ring end-cap.

**Max working pressure:**

BSP versions 8 bar (116 psi).

NPT versions 8,6 bar (125 psi).

**Max working temperature:** 45°C (113°F).

**Accessories on demand:** spanner, wall brackets, diffuser tubes, brass and plastic nipples, KIT AUTO (discharge automation kit), Lubrikit.

**Main materials:** Reinforced PP, PET.



JUNIOR TS

SENIOR TS MP

SENIOR DUPLEX TS

SENIOR M AB

SENIOR TS

MASTER TS

**DRAIN FUNNEL**  
Back-flow  
preventing device  
UNI EN 1717-11/2002